



## PRODUCT BULLETIN

### ▪ ENGINE OIL FLUSH

Nulon EOF is formulated to dissolve and dislodge harmful sludge, dirt, varnish and other contaminants that accumulate within an engine's lubrication system during normal operation.

Although modern engines are cleaner from an environmental aspect, all the pollutants of engine combustion previously released to the atmosphere are now recirculated within the engine. Consequently, lubricating oils have a much more difficult task in cleaning and suspending all of these additional contaminants.

When added to the crankcase oil prior to an oil and filter change, Nulon EOF greatly assists in ridding the engine of potentially damaging contaminants. Nulon EOF also frees sticky valves and hydraulic lifters. Thermal efficiency of the engine is also improved by ridding the engine of insulating sludge build-up. EOF provides a cleaner environment for fresh oil to operate, so the detergent dispersant and anti-oxidant additives in the new oil are not depleted as quickly.

#### Benefits:

- Cleans all lubricated components
- Reduces sludge, varnish and dirt contaminants
- Frees sticky valves and hydraulic lifters
- Improves overall engine efficiency
- Extends the service life of new oil
- Reduces the possibility of oil galleys being blocked, thus reducing the possibility of engine failure

#### Features:

- Nulon EOF is extremely simple to use and improves the environment in which lubricating oil operates. EOF is suitable for use with all synthetic and mineral oils
- Suitable for petrol, gas and diesel engines
- Safe to use in older engines
- Will not harm oil seals or gaskets

#### Directions for Use:

Add to engine crankcase oil immediately prior to an oil change. Run the engine at idle for 10 minutes. Stop engine and drain the oil while warm. Install new oil and filter.

#### Application Rates:

Add one 300 ml (10.14 US fl oz) bottle of Nulon EOF for every 5 litres (1.32 US gals) or part thereof of engine oil.

#### Warning:

Keep out of reach of children. Avoid contact with skin and eyes. Avoid contact with used oil.

#### First Aid and Safety Directions:

For advice contact the Poisons Information Centre (Ph. Australia 131 126; New Zealand 0800 764 766) or a doctor (at once). If swallowed, do NOT induce vomiting. Not to be used as a food container

#### Packaging:

300 ml bottle (12 bottles/carton) \* Part No. EOF